

MVF-016N

Diaphragm vacuum pumps

(Image coming soon)



Predictable

- Stable behaviour under real operating conditions.
- Fewer adjustments. Fewer deviations.
- Costs under control from day one.



Accessible

- Quick, straightforward maintenance.
- Direct access to critical components.
- No unnecessary dependencies.



Direct response

- Direct intervention, no middlemen.
- We act on the complete system to reduce downtime and ensure continuity.

BUILT FOR RELIABLE PLANT OPERATION

Design built around real-world operation

Optimised for continuous duty

Stability under process conditions

Hassle-free maintenance

Direct access to key components

Fewer points of failure

Components built to last

Thermal stability

Less operational wear

Configured to the application

Variable speed drives, monitoring, versions (ATEX, Aqua, O2), tailored filtration

MVF-016N

Diaphragm vacuum pumps



PERFORMANCE CURVE

(More details coming soon)

TECHNICAL SPECIFICATIONS

MVF-016N	
Nominal pumping speed	16.0 / 19.2 m ³ /h (50 / 60 Hz)
Ultimate pressure	150 mbar
Nominal motor rating	400 / 480 W (50 / 60 Hz)
Nominal motor speed	1400 / 1680 rpm (50 / 60 Hz)
Noise level (ISO 2151)	70 dB(A)
Approx. weight	20 kg
Dimensions (L x W x H)	375 × 200 × 310 mm

**NEED INFORMATION ABOUT MVF-016N?
FULL DETAILS ON OUR WEBSITE**

marpavacuum.com/en

Contact us
by scanning this QR code

